

Infra Red LED

LED19SC



Optically Immersed 1.9 μm LED in heat-sink optimised housing				LED19Sc
Peak wavelength	λ_{max}	μm	1.95 \pm 0.05	
Pulsed power at I=1 A	P_{pulsed}	mW	6.0 \pm 1.2	
CW power at I=200 mA	P_{CW}	mW	1.0 \pm 0.2	
Switching time	τ	ns	\leq 20	

Code	Thread	Emission size, mm	Lens material	Far-field pattern FWHM, deg.	Operation (storage) conditions, °C	Polarity
LED19Sc	M5 \times 0.5	\varnothing 3.3	Si	\leq 35	-25 - +60 (+80)	short wire or black point is negative
LED19TO8TEC			Si lens and quartz window			See fig. below

	LED19Sc	LED19TO8TEC
Product view		<p>1 TEC -; 2 TEC + 3 PD +; 6 PD - 4, 5 thermosensor</p>

- ✓ All devices are stressed at 80°C and I=200 mA (CW) for 10 hrs before final test and shipping.
- ✓ Beam divergence of the LEDs is small and thus we recommend adjusting LED position regarding the detector system before final evaluation/use of the devices.
- ✓ All data is valid for room temperature (22°C) and LED attached to a heatsink. A heatsink is important for normal LED operation especially in the CW mode.
- ✓ Available accessories include driver electronics and detectors.
- ✓ Available wavelengths include 1.9, 2.15, 3.0, 3.4, 3.6, 3.8, 4.2, 4.7, 5.5 and 7.0 μm .

