


UV-Air Probe with 0-5V Output and UVC Photodiode (SiC)

UV_Air_C_AMP0-5V_cable



Features of UV_Air_C_AMP0-5V_cable:

- Only for UVC measurement, e.g. for purification control, spectral sensitivity according to DVGW W294-3
- Filtered, silicon carbide based UV photodiode for extreme radiation hardness
- Integrated amplifier with 0..5V voltage output
- Offset and amplification factor are adjustable
- With M22 thread for comfortable mounting
- With Teflon diffuser for cosine correction
- Handy and solid stainless steel housing, IP65 at back
- 2m shielded cable

Probes from the **UV-Air** series are available with the following details:

Sensortype	Part Number
With broadband photodiode	UV_Air_ABC_Design
With UVC photodiode DVGW W 294-3	UV_Air_C_Design
With Erythema Sensor DIN 5050 ISO 17166/CIE S 007/E	UV_Air_UV-Index_Design

Design	Part Number
With 4-20mA output and 2m cable	UV_Air_Sensortype_AMP4-20mA_cable
With 4-20mA output and 5 pin connector	UV_Air_Sensortype_AMP4-20mA_plug
With 0-5V output and 2m cable	UV_Air_Sensortype_AMP0-5V_cable
With 0-5V output and 5 pin connector	UV_Air_Sensortype_AMP0-5V_plug
Without amplifier	UV_Air_Sensortype_cable

Please consider the following probe series:

- UV-Water (10bar water pressure resistant)
- UV-Cosine (with wide angle characteristic, cosine correction)
- UV-DVGW (probe compliant to DVGW W 294-3(2006))

page 1 [2]

UV-Air Probe with 0-5V Output and UVC Photodiode (SiC)


UV_Air_C_AMP0-5V_cable




Technical Data (T_a = 25 °C)

Parameter	Symbol	Value	Unit
Power supply	V _B	+7...24	V
Output signal	V _{OUT}	0...5	V
Power consumption	I _{max}	<30	mA
Linearity	L	2	%
Temperature drift	ΔT	0,03	W/m ² /K
Wavelength of max. Sensitivity	λ _{Smax}	270	nm
Sensitivity range (S=0.1*S _{max})	–	230 - 285	nm

Spectral Sensitivity (photodiode SG01S-C18)



Dimensions



Configuration:

Brown: V₀
 White: V₊
 Green: signal